



Dominator Series




Perfect for:

Rental Stores • Shopping Centers • Trucking • Schools • Marinas • Warehouses • Hospitals • Chemical Processors



The Dominator is built tough for rental and industrial uses, providing hot and cold water cleaning power in a compact, maneuverable design.



CONTROL PANEL

Simple control panel makes for easy and convenient operation.



COIL SYSTEM

Our exclusive "Cool Touch Coil" actually forms the combustion chamber, eliminating troublesome insulation and outside hot spots. It also allows for better air flow which in turn provides better fuel combustion and efficiency.



ACCUMULATOR ASSEMBLY

The Max Performance Accumulator Assembly, used on models with 2500 PSI or more, effectively manages high-pressure flow conditions that may ordinarily cause system failure.



OPTIONAL HOSE REEL

No more tangled hoses with our optional hose reel. The Dominator hose reel provides versatility by pivoting a full 360° and allowing up to 100' of hose.

MODEL

Gasoline Powered	GPM	PSI	HP	ENGINE	START	BURNER	COIL	BTU's	FUEL CONSUMPTION	DIMENSION	WEIGHT
MXDH3030HDOF	3.0	3000	9	HONDA	PULL	OIL FIRED	126', 1/2", Sch. 80	315,000	1.75 GPH	48"L x 32"W x 39"H	560 lbs
MXDH4030HDOF	4.0	3000	11	HONDA	ELECTRIC	OIL FIRED	126', 1/2", Sch. 80	434,000	2.25 GPH	48"L x 32"W x 39"H	560 lbs
MXDH3540HDOF	3.5	4000	13	HONDA	ELECTRIC	OIL FIRED	126', 1/2", Sch. 80	434,000	2.25 GPH	48"L x 32"W x 39"H	560 lbs
Electric Powered Direct Drive	GPM	PSI	HP	VOLTS/PHASE	AMPS	BURNER	COIL	BTU's	FUEL CONSUMPTION	DIMENSION	WEIGHT
MXDH2015EBOD	2	1500	2	115/1	20	OIL FIRED	126', 1/2", Sch. 40	170,000	1.25 GPH	48"L x 32"W x 40"H	420 lbs
MXDH3020EBOA	3	2000	4	220/1	20	OIL FIRED	126', 1/2", Sch. 80	315,000	1.75 GPH	48"L x 32"W x 40"H	430 lbs
MXDH4023EBOA	4	2300	6	220/1	25	OIL FIRED	126', 1/2", Sch. 40	434,000	2.25 GPH	48"L x 32"W x 40"H	590 lbs.
MXDH4030EBOA	4	3000	8	220/1	35	OIL FIRED	126', 1/2", Sch. 80	434,000	2.25 GPH	48"L x 32"W x 40"H	450 lbs

STANDARD FEATURES

- Heavy duty roll cage frame with lifting bar
- Stainless steel coil wrap & control panel
- Heavy-duty triplex plunger oil bath pump
- Corrosion-proof 8 gal fuel tank
- Fuel water separator
- Pulsation dampener
- Pneumatic tube wheels
- Adjustable axles for balance of weight
- Detergent injector
- 50' high pressure hose with quick disconnects
- Four color-coded quick-change spray nozzles
- Dual lance wand for variable pressure
- Hose reel mounting bracket

OPTIONS

- Hour meter
- Front swivel casters
- Steam option
- Adjustable temperature control
- Auto on/off with 30 sec. delay (electric models only)
- Hose reel
- UL1776 listed
- Painted coil wrap

5 - 1 YEAR LIMITED WARRANTY

- 5 years on pump, Cool Touch Coil and frame
- 2 years on gasoline engines
- 1 year - 90 days on remaining components



MAX-PERFORMANCE EQUIPMENT

200 EXECUTIVE DRIVE SUITE 160 WEST ORANGE, NJ 07052 USA

TEL. +1-973-325-3838 FAX +1-973-325-7974

Email: sales@max-performanceltd.com

#MXD3-08